



Mess- und Prüftechnik. Die Experten.

Ihr Ansprechpartner /  
Your Partner:

**dataTec AG**  
E-Mail: [info@datatec.eu](mailto:info@datatec.eu)  
>>> [www.datatec.eu](http://www.datatec.eu)

EXKLUSIVER  
VERTRIEBSPARTNER  
VON

**STS** electronic

# Hipot Tester **HA 6600H, HA 6680U**

Our Hipot tester offer you exactly what you need for your high-voltage testing - from manual stand-alone devices to automatic multifunctional devices.

Our tester generally offer a freely programmable test voltage level of up to 5500 V AC or 6000 V DC at up to 100 mA. Our products also allow you to freely set the type and duration of the test and the maximum leakage current.

With all of our high-voltage tester, an insulation resistance test is possible in addition to the high-voltage test, as both tests are usually carried out at the same points on the electrical devices.

The products impress with a wide range of technical features:

- Ideal for fast, cost-effective and convenient safety testing
- National and international standards (IEC, EN, UL, VDE, etc.)
- Simple instructions make operation intuitive and efficient
- A fully automatic test plan can be created for each product
- Can also be used by non-professionals
- Fully electronic high-voltage generator, which ensures accurate and fast testing

		<b>HA 6600H</b>	<b>HA 6680U</b>
		Desktop device	19" rack device
<b>High Voltage Test AC</b>	Voltage Range	100 V - 5500 V	
	Current Range	0 mA - 20 mA	
	Short Circuit Current	>20 mA	
<b>High Voltage Test DC</b>	Voltage Range	100 V - 6000 V	
	Current Range	0 mA - 20 mA	
	Short Circuit Current	>20 mA	
	Residual Ripple	< 3%	
<b>Insulation Measurement DC</b>	Voltage Range	100 V - 6000 V	
	Measuring Range	100 kΩ - 50 GΩ	
	Residual Ripple	< 3%	
<b>Digital Interface 24 VDC</b>	Input	4	
	Output	4	
<b>Mains Supply</b>	Voltage	90 V - 250 V	
	Frequency	50 Hz / 60 Hz	
<b>Interfaces</b>	USB	✓	
	Ethernet / LAN	✓	
<b>Operation</b>	Touch for Input	7"-TFT colour display	
<b>Dimensions and Weight (approx.)</b>	Height	148 mm   5.8 in	133 mm   5.2 in
	Width	420 mm   16.5 in	482 mm   19.0 in
	Depth	508 mm   20.0 in	439 mm   17.3 in
	Weight	20,4 kg   45.0 lbs	20,4 kg   45 lbs