


EA-ELR 21000-80

High Speed Regenerative Load

DATASHEET



Features

- Input: 380 V - 480 V, $\pm 10\%$, 3 ph AC
- Active power factor correction, typical 0.99
- Regenerative with energy recovery into the grid
- Very high efficiency of up to 95.1%
- High performance with up to 30 kW per unit
- Voltage range 0 - 1000 V
- Current range 0 - 80 A
- Flexible power regulated DC input stages (autoranging)
- Overpower feature allowing 125% power (within nominal voltage and current) for 500 ms. Optimized for 800 V systems.
- Regulation modes CV, CC, CP, CR, with fast crossover
- Digital regulation, high resolution with 16 bit ADCs and DACs, selection of voltage control speed
- Galvanically isolated Share-bus for parallel operation
- Master-Auxiliary bus for parallel operation
- Built-in EtherCAT interface with 1 ms communication speed
- Command languages and drivers: SCPI, ModBus, LabVIEW, IVI

Built-in interfaces

- USB
- Ethernet 1 Gbit/s
- EtherCAT
- CAN FD
- Master-Auxiliary bus
- Share-bus
- USB host (front panel)
- Digital In/Out

Software

- EA Power Control

Options

- Water cooling in stainless steel

Energy recovery

The energy consumed in load mode is fed back into the connected grid with efficiencies of up to 95%. Unlike conventional loads that dissipate energy as heat, the regenerative design helps reduce energy costs. Lower heat generation also reduces cooling requirements and associated air conditioning costs. For many applications, a single device may be sufficient, helping reduce investment and installation costs.



Mess- und Prüftechnik. Die Experten.

**Ihr Ansprechpartner /
Your Partner:**

dataTec AG
E-Mail: info@datatec.eu
datatec.eu



Elektro-Automatik



The principle of energy recovery

Figure 1 demonstrates, based on a typical application, how a device under test consumes energy from the mains, converts it to DC and feeds that into an EA device. The high-speed regenerative load EA-ELR 21000-80 4U HS converts this energy back into an AC current and feeds it back into the grid.




Figure 1

Interfaces

The EA-ELR 21000-80 4U HS includes the most commonly used interfaces and ports, all of which are galvanically isolated from the DC side. Communication speeds of up to 1 ms are supported. The following digital interfaces are available:

- USB
- Ethernet 1Gbit/s
- EtherCAT
- CAN FD
- USB host

In addition, there are 3 digital inputs, 3 relay contacts and 3 temperature sensor inputs.

A Master-Auxiliary bus and Share bus are available for expanding the devices as a high-performance system. With these interfaces, the system works like a single device with symmetrical load sharing.

DC connection

DC connections are made using copper blade terminals located on the rear of the device. For higher power requirements, multiple devices can be connected in parallel. A protective cover is included to help prevent accidental contact.

Master-Auxiliary bus and Share bus

If the integrated Master-Auxiliary bus and Share bus are used, a multi device system behaves as a single device. Both buses are connected between each device. With the Master-Auxiliary bus the system data, such as total power and total current, are collected and shown on the master device. Warnings and alarms of the auxiliary devices are shown clearly in the display. The Share bus provides an equal load distribution to the individual devices.

General Specifications

AC Input

Voltage, Phases	380 - 480 V, $\pm 10\%$, 3 ph AC
Frequency	45 - 65 Hz
Power Factor	ca. 0.99
Leakage Current	<10 mA
Inrush Current ¹	@400 V: ca. 54 A per phase
Overvoltage Category	II

Protective Functions

OVP	Overvoltage protection, adjustable 0 - 110% U_{Nominal}
OC	Overcurrent protection, adjustable 0 - 110% I_{Nominal}
OPP	Overpower protection, adjustable 0 - 110% P_{Nominal} Overpower protection, adjustable 110 - 125% P_{Nominal} ⁴
OT	Overttemperature protection (DC terminal shuts down in case of insufficient cooling)

DC Input Dynamic

di/dt performance 1 Device	Stepwith	Basic Configuration ²	Enhanced Performance Settings ²	Max. Performance Settings ²
	10% - 60% 4 A - 22 A 3.2 kW - 17.6 kW	di/dt: 0.5 A/ μ s Current Overshoot: 20%	di/dt: 0.8 A/ μ s Current Overshoot: 30%	di/dt: N/A Current Overshoot: N/A
	50% - 100% 19 A - 37 A 15.2 kW - 29.6 kW	di/dt: 0.5 A/ μ s Current Overshoot: 40%	di/dt: 0.8 A/ μ s Current Overshoot: 55%	di/dt: N/A Current Overshoot: N/A
	10% - 100% 4 A - 37 A 3.2 kW - 29.6 kW	di/dt: 1.1 A/ μ s Current Overshoot: 30%	di/dt: 1.3 A/ μ s Current Overshoot: 30%	di/dt: 1.5 A/ μ s Current Overshoot: 80%
	10% - 120% ³ 4 A - 47 A 3.2 kW - 37.6 kW	di/dt: 1.5 A/ μ s Current Overshoot: 25%	di/dt: 1.7 A/ μ s Current Overshoot: 20%	di/dt: 1.9 A/ μ s Current Overshoot: 45%

di/dt performance 2 Devices	Stepwith	Basic Configuration ²	Enhanced Performance Settings ²	Max. Performance Settings ²
	10% - 60% 7 A - 45 A 5.6 kW - 36 kW	di/dt: 1.1 A/ μ s Current Overshoot: 30%	di/dt: 1.6 A/ μ s Current Overshoot: 35%	di/dt: N/A Current Overshoot: N/A
	50% - 100% 37 A - 75 A 29.6 kW - 60 kW	di/dt: 1.3 A/ μ s Current Overshoot: 45%	di/dt: 1.6 A/ μ s Current Overshoot: 50%	di/dt: N/A Current Overshoot: N/A
	10% - 100% 7 A - 75 A 5.6 kW - 60 kW	di/dt: 2.3 A/ μ s Current Overshoot: 35%	di/dt: 2.7 A/ μ s Current Overshoot: 35%	di/dt: 3.1 A/ μ s Current Overshoot: 50%
	10% - 120% ³ 7 A - 93 A 5.6 kW - 74.4 kW	di/dt: 3.0 A/ μ s Current Overshoot: 35%	di/dt: 3.3 A/ μ s Current Overshoot: 35%	di/dt: 3.7 A/ μ s Current Overshoot: 45%

di/dt performance 4 Devices	Stepwith	Basic Configuration ²	Enhanced Performance Settings ²	Max. Performance Settings ²
	10% - 60% 15 A - 90 A 12 kW - 72 kW	di/dt: 1.6 A/μs Current Overshoot: 10%	di/dt: 2.0 A/μs Current Overshoot: 15%	di/dt: 2.9 A/μs Current Overshoot: 30%
	50% - 100% 75 A - 150 A 60 kW - 120 kW	di/dt: 1.9 A/μs Current Overshoot: 20%	di/dt: 2.4 A/μs Current Overshoot: 20%	di/dt: 3.1 A/μs Current Overshoot: 30%
	10% - 100% 15 A - 150 A 12 kW - 120 kW	di/dt: 3.3 A/μs Current Overshoot: 15%	di/dt: 3.7 A/μs Current Overshoot: 15%	di/dt: 4.5 A/μs Current Overshoot: 20%
	10% - 120% ⁴ 15 A - 187 A 12 kW - 150 kW	di/dt: 4.3 A/μs Current Overshoot: 15%	di/dt: 4.6 A/μs Current Overshoot: 10%	di/dt: 5.5 A/μs Current Overshoot: 20%

di/dt performance 8 Devices	Stepwith	Basic Configuration ²	Enhanced Performance Settings ²	Max. Performance Settings ²
	10% - 60% 30 A - 180 A 24 kW - 144 kW	di/dt: 3.4 A/μs Current Overshoot: 10%	di/dt: 4.7 A/μs Current Overshoot: 15%	di/dt: 6.4 A/μs Current Overshoot: 35%
	50% - 100% 150 A - 300 A 120 kW - 240 kW	di/dt: 4.1 A/μs Current Overshoot: 25%	di/dt: 5.6 A/μs Current Overshoot: 20%	di/dt: 6.8 A/μs Current Overshoot: 45%
	10% - 100% 30 A - 300 A 24 kW - 240 kW	di/dt: 7.0 A/μs Current Overshoot: 15%	di/dt: 7.8 A/μs Current Overshoot: 10%	di/dt: 10.0 A/μs Current Overshoot: 25%
	10% - 120% ³ 30 A - 375 A 24 kW - 300 kW	di/dt: 9.4 A/μs Current Overshoot: 20%	di/dt: 10.1 A/μs Current Overshoot: 10%	di/dt: 12 A/μs Current Overshoot: 20%

1. Calculated for the peak value of the stated voltage including 10% tolerance, at 23°C ambient and first switch-on (cold start).

2. Measured with following configuration:

- cable length: 3 m
- cable twisted together
- cable diameter: 25 mm²
- number of cables: 1 per pole (2 per device)
- Voltage: 800 V

3. 120% with overpower feature enabled.

4. For Overpower feature.

Display & Measurement Accuracy

Voltage ≤0.05% FS

Current ≤0.1% FS

Insulation

AC Input to DC Terminal 3750 Vrms (1 minute, creepage distance >8 mm)

AC Input to Case (PE) 2500 V DC

DC Terminal to Case (PE) See model table

DC Terminal to Interfaces 1500 V DC

Communication Interfaces

Rear, Galvanically Isolated USB, Ethernet (1 GBit), EtherCAT, CAN FD, all for communication

Communication Speed ≤1 ms⁴

Front, Galvanically Isolated USB host, for data acquisition

Digital In/Out	
Built-in, Galvanically Isolated	16 pole
Inputs	3× independent, user-configurable
Outputs	3× independent, as dry contact
Sensor Inputs	3× independent, for temperature sensor

Device Configuration	
Parallel Operation with Share Bus	Up to 64 units of the same series

Safety and EMC	
Safety	EN 61010-1 IEC 61010-1 BS EN 61010-1
EMC	EN 55011, class A, group 1 CISPR 11, class A, group 1 EN 61326-1 including tests according to: - EN 61000-4-2 - EN 61000-4-3 - EN 61000-4-4 - EN 61000-4-5 - EN 61000-4-6
Appliance Class	I
Ingress Protection	IP20

Environmental Conditions	
Operating Temperature	0 - 35 °C (32 - 95 °F)
Storage Temperature	-20 - 70 °C (-4 - 158 °F)
Humidity	≤80% relative humidity, non-condensing
Altitude	≤2000 m (≤6,600 ft)
Pollution Degree	2

Mechanical Construction	
Cooling	Forced air flow from front to rear (temperature controlled fans), optional water cooling
Dimensions (W x H x D)	Chassis: 483 mm (19 in) × 177 mm (4U) × 668 mm (26.3 in) Overall Depth: min. 802 mm (min. 31.6 in)
Weight	50 kg (110 lb)
Weight with Water Cooling	56 kg (126 lb)

DC Input

Voltage Range	0 - 1000 V
U_{Min} for I_{Max} (sink)	36.5 V
Current Range	0 - 80 A
Power Range	Nominal: 0 - 30000 V With Overpower: 0 - 37500 W
Output Capacitance	80 μF
Efficiency Sink/Source (up to) ¹	95.1 %

AC Input

P_{Max}	33 kW
Phase Current ²	≤ 56 A

Insulation

Negative DC pole <-> PE	± 1500 V DC
Positive DC pole <-> PE	+2000 V DC


Product Codes

Standard	33530406
Standard + Water Cooling	On request


1. At 100 % power and 80 % output voltage.

2. Calculated for the default AC supply voltage in the stated range, minus 10 % tolerance, at maximum output power and 10 % power loss from AC to DC.

Technical Drawings EA-ELR 21000-80 4U HS




Front Panel Description EA-ELR 21000-80 4U HS




1. Power switch
2. TFT control interface, interactive operation and display
3. Rotary knob with push-button action, for settings and control
4. USB host, uses USB sticks for data logging and sequencing
5. Rotary knob with push-button action, for settings and control
6. On / Off push-button with LED status display

Rear Panel Description EA-ELR 21000-80 4U HS




1. Ethernet interface
2. EtherCAT ports
3. Remote sense connectors
4. Share bus connectors to set up a system for parallel connection
5. DC output connector (copper blades)
6. AC input connector
7. Digital In/Out (16 pole connector)
8. CAN FD interface
9. USB interface

Front Panel Description EA-ELR 21000-80 4U HS with Water Cooling option



1. Power switch
2. TFT control interface, interactive operation and display
3. Rotary knob with push-button action, for settings and control
4. USB host, uses USB sticks for data logging and sequencing
5. Rotary knob with push-button action, for settings and control
6. On / Off push-button with LED status display

Rear Panel Description EA-ELR 21000-80 4U HS with Water Cooling option



1. Ethernet interface
2. EtherCAT ports
3. Remote sense connectors
4. Share bus connectors to set up a system for parallel connection
5. DC output connector (copper blades)
6. AC input connector
7. Digital In/Out (16 pole connector)
8. CAN FD interface
9. USB interface
10. Water inlet/outlet

Contact Information:

Australia 1 800 709 465
Austria* 00800 2255 4835
Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Belgium* 00800 2255 4835
Brazil +55 (11) 3530-8901
Canada 1 800 833 9200
Central East Europe / Baltics +41 52 675 3777
Central Europe / Greece +41 52 675 3777
Denmark +45 80 88 1401
Finland +41 52 675 3777
France* 00800 2255 4835
Germany* 00800 2255 4835
Hong Kong 400 820 5835
India 000 800 650 1835
Indonesia 007 803 601 5249
Italy 00800 2255 4835
Japan 81(3) 6714 3086
Luxembourg +41 52 675 3777
Malaysia 1 800 22 55835
Mexico, Central/South America and Caribbean 52 (55) 88 69 35 25
Middle East, Asia, and North Africa +41 52 675 3777
The Netherlands* 00800 2255 4835
New Zealand 0800 800 238
Norway 800 16098
People's Republic of China 400 820 5835
Philippines 1 800 1601 0077
Poland +41 52 675 3777
Portugal 80 08 12370
Republic of Korea +82 2 565 1455
Russia / CIS +7 (495) 6647564
Singapore 800 6011 473
South Africa +41 52 675 3777
Spain* 00800 2255 4835
Sweden* 00800 2255 4835
Switzerland* 00800 2255 4835
Taiwan 886 (2) 2656 6688
Thailand 1 800 011 931
United Kingdom / Ireland* 00800 2255 4835
USA 1 800 833 9200
Vietnam 12060128

* European toll-free number. If not accessible, call: +41 52 675 3777

Rev. 02.2022



Mess- und Prüftechnik. Die Experten.

**Ihr Ansprechpartner /
Your Partner:**

dataTec AG

E-Mail: info@datatec.eu

datatec.eu



Elektro-Automatik

Find more valuable resources at TEK.COM

Copyright © Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.
082526 SBG 1EW-74286-0

